



KEFLEX™ Gold Series Reducing braided flexible hose assemblies are constructed of stainless steel annular corrugated metal hose surrounded with a woven braid of high tensile stainless steel. The KEFLEX™ Gold Series is the premier product in the industry.

Standard end fittings for KEFLEX™ Gold Series units are 150# carbon steel flanges. These assemblies are intended for normal to severe pump vibrations. Misalignment should not exceed 1/8" total. Maximum operating temperature is 850°F. For higher pressures or temperatures, consult the factory.

### **Features:**

- ▶ *Integral Concentric Reducer*
- ▶ *Integral 150# Carbon Steel Flanges*
- ▶ *Variety of lengths and flange combinations*
- ▶ *Custom or standard material selection*
- ▶ *Maximum vibration absorption*

### **Benefits:**

- ▶ *Eliminates cost of separate reducer*
- ▶ *Eliminates cost of flanges, gaskets & bolting hardware*
- ▶ *Meets most installation requirements*
- ▶ *Meets most application needs*
- ▶ *Increases equipment life*

Keflex Part Number	Large End & Hose Size	Small End Size	OAL	Max Working PSI @ 70°F*	Approx Weight (lbs.)
F020KFCS014RF	2"	1 1/2"	13"	435	12
F024KFCS014RF	2 1/2"	1 1/2"	13"	350	15
F024KFCS020RF	2 1/2"	2"	13"	350	15
F030KFCS020RF	3"	2"	13"	310	18
F030KFCS024RF	3"	2 1/2"	13"	310	19
F040KFCS020RF	4"	2"	13"	230	22
F040KFCS024RF	4"	2 1/2"	13"	230	25
F040KFCS030RF	4"	3"	13"	230	25
F050KFCS024RF	5"	2 1/2"	16"	190	30
F050KFCS030RF	5"	3"	16"	190	30
F050KFCS040RF	5"	4"	16"	190	34
F060KFCS030RF	6"	3"	17"	165	38
F060KFCS040RF	6"	4"	17"	165	40
F060KFCS050RF	6"	5"	17"	165	42
F080KFCS040RF	8"	4"	18"	185	55
F080KFCS050RF	8"	5"	18"	185	58
F080KFCS060RF	8"	6"	18"	185	60
F100KFCS060RF	10"	6"	20"	165	85
F100KFCS080RF	10"	8"	20"	165	95
F120KFCS100RF	12"	10"	22"	125	125

***Keflex is your single source for braided hose assemblies. Check out our:***

- ▶ Gold Plus Series flexible hose
- ▶ Gold Series reducing hose
- ▶ Silver Series flexible hose
- ▶ Ke-Loop L, U & V expansion loops
- ▶ HPH Series Heat Pump / Water hose

