



BILL OF MATERIAL	
DESCRIPTION	MATERIAL
'A' COVER & TUBE	EPDM
'B' FEMALE UNION	COATED DUCTILE IRON
BODY REINFORCING	NYLON
STABILIZING RING	CARBON STEEL
CABLES	COATED CARBON STEEL

MAX. TEMPERATURE: 230° F

TAG #	LOC.	DIA[IN.]	KEFLEX PART #	DESIGN PRESS @170 F	OAL	AXIAL COMP.	AXIAL EXT.	LATERAL DEFL.	ANGULAR DEFL.
		3/4"	F006CEE080	150	8"	7/8"	1/4"	7/8"	32°
		1"	F010CEE080	150	8"	7/8"	1/4"	7/8"	25°
		1 1/4"	F012CEE080	150	8"	7/8"	1/4"	7/8"	20°
		1 1/2"	F014CEE080	150	8"	7/8"	1/4"	7/8"	17°
		2"	F020CEE080	150	8"	7/8"	1/4"	7/8"	13°
		2 1/2"	F024CEE080	150	8"	7/8"	1/4"	7/8"	10°
		3"	F030CEE080	150	8"	7/8"	1/4"	7/8"	8°

DRAWN	DJM	KEFLEX PRODUCTS 1425 LAKE AVENUE WOODSTOCK, ILLINOIS 60098			
DATE	30APRIL15				
CHECKED		TITLE EPDM TWIN SPHERE CONNECTOR WITH FEMALE THD. UNION			
APPROVED	DG	SIZE	FSCM NO.	DWG NO.	REV
QC		A	87738	SUBMITTAL DRAWING	A
FILE	SUBNTSC100.DWG	SCALE NONE		SHEET 1 OF 1	
JOB	EJ2				

SUBMITTED BY:	DATE
CLIENT APPROVAL	DATE